

# SOLISTA LX WALL LED BEACON

Alarm devices

Product Datasheet

EN 54-23 Coverage Reference: W-2.4-7.5

## Features

- Ultra low current consumption
- Up to 7.5m coverage (135m<sup>3</sup>)
- 0.5Hz or 1Hz flash rate
- Coverage switch to 2.5m
- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to 0.5Hz to reduce current consumption
- Reduces power consumption by up to 50%

## Description / Application

The Solista LX Wall has a slim line design. The device is available in a red body colour and with a shallow or deep base, the Solista LX Wall is suitable for a variety of applications.

The Solista LX Wall has a unique lens design that distributes light to achieve the required illumination, whilst using minimum current.



Product Name	Part number	Description
Solista LX Wall LED Beacon	116-4340-007.0001	Solista LX Wall LED Beacon, Wall mounted, deep base
Solista LX Wall LED Beacon	116-4340-007.0007	Solista LX Wall LED Beacon, Wall mounted, shallow base

Technical specifications (for complete product; wall base and sounder)	
Mounting Type	Wall
Voltage	9 – 60Vdc
Current	10 - 25mA dependent on setting
Coverage (y)	7.5m (Switchable to 2.5m)
Mounting Height (x)	2.4m (max)
Coverage Volume Code	W-2.4-7.5
Coverage Volume	135m <sup>3</sup> (15m <sup>3</sup> )
Flash Rate	1Hz (Switchable to 0.5Hz)
Operating Temperature	-25°C - +70°C
Monitoring	Reverse Polarity
Protection	IP33C Shallow Base, IP65 Deep Base
Weight	100g
Body Colour	Red
Flash Colour	Red

## Dimension Drawing

